


NEUP Cement Calcination Project Updates

C. Balbier, S. Bucks, A. Dahanayake, O. Felegy, J. P. Gevaudan, S. Lee, M. Nieto, S. Talabi.



March 2025 – March 2026




KEN AND MARY ALICE
LINDQUIST DEPARTMENT OF
NUCLEAR ENGINEERING

FUTURE

VISION

OPPORTUNITY


Overview of cement process



Goals

- Feasibility of nuclear energy insertion in the cement process.
 - Energetic and economic viability.
 - Study of the effect of insertion in calcination chemistry.
 - Identify process integration strategy.

Cement plant energy balance




Assumptions:

- No additional reactions
- Instantaneous reactions at 850 and 1450 °C
- All gases at 1 atm
- Isentalpic operation


Kiln energy balance

- Kiln operation without combustion requires less energy.
- No need to heat up combustion byproducts.
- Effect is more pronounced for high air flows and high air temperatures.
- Restrictions due to air flow cap on preheater tower.





Calciner energy balance

- More air flow, less fuel, since now gas provides heating.
- Insensitive to inlet composition.
- The combustion system has slightly less energy demand.





Mineral models stagnant calcination benchmark




- Secondary Electron (SE) Micrographs of (a) $\text{Mg}(\text{OH})_2$ and (b) $\text{Mg}_5(\text{CO}_3)_4(\text{OH})_2 \cdot 5-6\text{H}_2\text{O}$ Calcined Raw Materials. Scale bars within each image correspond to the following lengths: (a) $1 \mu\text{m}$ and (b) $3 \mu\text{m}$.
- The hydroxide starting material was composed of 99.9 % $\text{Mg}(\text{OH})_2$ (brucite) and 0.1 % MgO (periclase) as evidenced by the Rietveld-refined, X-ray diffraction (XRD) pattern.

Effect of MgO nanocrystallites agglomeration on thermal decomposition




Compared to HMC calcination, MH calcination formed smaller MgO clusters particles with median sizes 6.37 – 6.41 μm and larger surface areas (40.8 – 149.7 m^2/g). As the calcination degree increased from 26.6% to 90.6%, MgO agglomerates with similar size and an increasing surface area formed.

Actual kiln feed characterization



- The initial mineralogy (shown in Figure) of the kiln feed shows a significant calcite, CaCO_3 , (68.2 wt.%) content and secondary contents of muscovite, $\text{KAl}_3\text{Si}_3\text{O}_{10}(\text{OH})_2$, (9.5 wt.%) and dolomite, Ca,MgCO_3 , (3.4wt.%).
- The particle size distribution of the kiln-feed sample exhibits a median diameter (D50) of 26.9 μm , with its fines and coarse tails extending from 3.59 μm (D10) to 142 μm (D90)


Kiln feed static calcination experiments




- From 425 °C to 525 °C, the kiln feed is effectively inert, with conversion stuck below 0.2 % and BET surface area steady near $2.7 \text{ m}^2 \text{ g}^{-1}$, so the preheater contributes little beyond moisture removal
- Meaningful calcination only begins above $\sim 700 \text{ }^\circ\text{C}$, and the balance between sintering and gas-driven porosity will ultimately dictate kiln energy efficiency and clinker reactivity.

State of System Design

- Two gas inlet (air and CO₂) with oscillation capabilities
- 24" x 4" OD test section
- Designed for 800 °C at 10-20 SLM
- CO₂ exit concentration monitoring up to 20 v%
- 17 thermocouple measurements
- Gauge and differential pressure measurements of test section




CAD Model of System




Partially Insulated Experimental Setup

Fluidization Testing


- First tests with silver coated hollow glass particles at room temp.
- Expected velocities
 - $U_{min. fluidization} = 1.35 \text{ mm/s}$
 - $7.2 \text{ mm/s} < U_{turb. fluidization} < 9.3 \text{ mm/s}$
- Photron NOVA high speed camera at 50 FPS, 12.3 px/mm
- Frame is 84 mm wide (83% of test section)
- ROI is centered on test section, 12.7 x 25.4 mm




0.6 SLPM (1.34 mm/s avg.)



3.7 SLPM (8.28 mm/s avg.)



6.0 SLPM (13.4 mm/s avg.)




PIV Average Vertical Velocity in ROI

- Particle velocity agrees well with 6 SLPM case → beyond fluidization particles track with air
- Particle velocity below prediction for 3.7 SLPM case → fluidization
- Particle velocity is negligible for 0.6 SLPM case → very little fluidization

Results presented at NURETH-21 in Busan, South Korea

Fluidization Testing


- Move to room temperature tests with real calciner feed particles from Heidelberg Materials plant in Nazareth, PA
- Fluidization is proving difficult due to particle size and tunneling effects
- Currently exploring optimizing flow oscillations to promote fluidization



25 SLM Gas Flow, 250 FPS at 0.2x speed

Moving to High Temperature

- System goal of 800 °C operation
- Sealing the sight glass at high temperatures is proving to be difficult



High Temperature Shakedown with No Particle Loading

Next steps

- Process simulation with varying proportions of primary, secondary, and tertiary air, as well as introduction of nO-combustion heat input to the kiln (nucleoelectric).
- Process optimization.
- Economical feasibility evaluation.
- Testing of experimental column at high temperature and calcination kinetics evaluation with different CO₂ feed contents.

Acknowledgements

This material is part of work sponsored by the Department of Energy, Nuclear Energy University Program grant number DE-NE0009484.

This material is based upon work supported under a Department of Energy, Office of Nuclear Energy University Nuclear Leadership Program Graduate Fellowship. Any opinions, findings, conclusions, or recommendations expressed in this publication are those of the author(s) and do not necessarily reflect the views of the Department of Energy Office of Nuclear Energy.