Liquid Salt Experimentation to Support FHR and MSR Development

Graydon Yoder

Reactor and Nuclear Systems Division Oak Ridge National Laboratory






Liquid Salt Test Loop

- Forced convection facility
- Designed to perform multiple types of tests
 - Initial testing heat transfer in a salt cooled pebble bed
 - Potential testing
 - Pump performance
 - Instrument testing
 - Etc.

Salt	FLiNaK
Operating Temperature	≤700°C
Flow rate	≤4.5 kg/s
Operating pressure	Near atmospheric
Material of construction	Inconel 600
Loop volume	75 liters
Power	~20 kW trace 200 kW induction
Primary piping ID	2.67 cm (1.05 in.)





Two Fluoride Salt Cleanup

Systems

Designed to purify commercial salts

- Batch processes:
 - Dedicated HF, H₂ supplies
 - Processing crucible
 - Off-gas clean-up systems
- Large scale process (160kg):
 - FLiNaK (1st operation summer 2016)
 - Others [ZrF₄ salts (KF, NaF)]
 - (not Be or fuel salts)
- Bench scale process (4kg)
 - FliBe salt (operational summer 2017)
 - Can handle U and limited rad material in bldg.
 - Glove box includes cooler and well: small heated tests



4 kg system









Other Molten Salt Facilities Are Available to Support Salt


Reactor Technology

Molten Salt Cell





Observation of 700°C Molten Salt During Testing



Flow Calibration Test Stand

- Designed to calibrate flow meter(s)
 - ~120 L, ≤710 C, ≤ 30 psig
 - ~0.5-4.5 m/s (1" pipe)
- Potential uses:
 - Heat transfer testing
 - freezing tests
 - Oil similitude test
 - Natural circulation setup, ~7.5m
- Status: all major parts acquired;
 I&C and plumbing needs installed



Other facilities

Forced convection FLiBe loop being designed

Salt infrastructure

- Salt Chemistry
- Corrosion and materials compatibility
- Salt property measurement
- Instrumentation development

. . . .